




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 29/06, 29/12	A1	(11) International Publication Number: WO 99/22501 (43) International Publication Date: 6 May 1999 (06.05.99)
<p>(21) International Application Number: PCT/EP98/06752</p> <p>(22) International Filing Date: 23 October 1998 (23.10.98)</p> <p>(30) Priority Data: 197 47 583.3 28 October 1997 (28.10.97) DE</p> <p>(71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).</p> <p>(72) Inventors: SKAGERWALL, Roger; Yrkesvägen 15, S-122 31 Enskede (SE). NYGREN, Kaj; Kungsklippan 11 ltr, S-112 25 Stockholm (SE).</p> <p>(74) Agents: VON FISCHERN, Bernhard et al.; Hoffmann . Eitle, Arabellastrasse 4, D-81925 Munich (DE).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>

(54) Title: COMMUNICATION SYSTEM AND METHOD



(57) Abstract

Communication system and method for linking each of a plurality of tagged objects to information services stored in a network. The system provides means to read an object tag or one of the objects and means, to retrieve information about the object stored on storage means located at arbitrary places. To facilitate the retrieval of information, directory means are provided storing object data associating each of the objects with information services. In order to be able to handle a virtually arbitrary number of objects and information services, the directory means comprises a plurality of directory servers, each storing part of data base of the object data. The object data is distributed according to a defined scheme onto the plurality of directory servers in order to be able to identify the directory server storing object data associated with a particular read object tag.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Communication System and Method

[Field of the Invention]

5

The present invention relates to a system and method of communicating information in a network, and in particular, the present invention relates to a system for communicating information, related to a plurality of tagged objects, in a network.

10

[Background of the Invention]

15

20

25

In recent years, data communication techniques have evolved tremendously. Electromechanical equipment for communicating information over larger distances is now widely replaced by digital systems using semiconductor switches. With the availability of cheap data processing capacity in today's world, it is now possible for virtually everyone to not only communicate voice and audio signals but also data stored on computers, data bases, etc. Especially with the advent of computer networks, such as the Internet, connecting computers virtually all over the world, easy and inexpensive access to digital information becomes possible worldwide.

30

The Internet and similarly other networks can be used for a variety of different applications. It is, for example, possible to retrieve information about a specific topic by accessing files which may be physically located at arbitrary places, essentially worldwide. The files may contain text, audio signal, images, video or data related to applications.

35

In order to be able to access the files it is required to know the name of the documents and further, it is required

to know the addresses of network computers storing the documents. However, in many cases, information about the name and location of documents related to a desired topic or physical object is not available and, means for
5 retrieving information about possible locations of documents or applications related to the topic are required. Therefore, on most common networks various applications are available, to assist an user in identifying names of documents as well as addresses of
10 servers storing the documents related to the object.

Generally, the assisting applications perform a more or less detailed network search based on a keyword or sets of keywords provided by the user. A search result typically
15 is a list of addresses and links to servers storing information related to the desired topic. The user can select each record of the list and retrieve associated documents or services. In many cases, however, it will turn out that a very long list of addresses and links is
20 returned, but only a small number thereof is actually related to the desired topic. Key words supplied to a search application will often result in lists with thousands of entries and many entries of the list will only intermediately be related to the object or not at
25 all.

Retrieving information from a network can therefore be a tedious and time-consuming task, and the result might not be satisfying. This situation is further severed by the
30 swift growth of such networks.

There might be essentially two reasons causing the difficulty for a user to retrieve information about a specific object in. Even if the user knows some key facts
35 about the desired object, the search might still miss important information concerning the object and secondly,

often key information about the desired object is lacking and it therefore is not possible for the user to specify proper search terms, even if he knows which object he wants to retrieve information for. The user will also face the problem that it is not possible to get a determined answer whether desired information is available on the network or not, i.e., the information may exist, even if the conducted search failed.

10 It is therefore desirable to design a system, which readily delivers focused information about a certain topic or object without the need of performing time consuming network searches with sophisticated arrangements of search terms, in order to narrow down the number of "hits".

15 In the physical world, a large number of different objects, manmade or natural, exists and similarly, in the virtual world of a computer network information exists about virtually all physical objects. However, as outlined before, it is difficult to retrieve information related to a specific object. Thus there is a need for a system, which links physical objects with services in the information space.

25 A number of proprietary systems is known from daily life, which allow to connect a limited number of objects to information about the objects. For example, such systems may link car spare parts to information of a data base. A part number may be entered into the system and drawings, information about availability, price, etc., is returned. Similar systems are encountered supermarkets. The systems are able to display information related to an object under investigation or to account for sold items, prices, etc.

35 However, all of the above systems have several limitations regarding scalability with respect to the number of

objects and associated information services, robustness and generality.

Further, "broken" links, i.e., links and addresses stored
5 by a user at one point in time and which are not any
longer valid, pose a problem in computer networks. The
location of information or services, i.e., the address of
the computer of the network storing the information or
service, as well as filenames usually change over time due
10 to a rearrangement of servers, network addresses and the
like. In this case, a called address or link for
retrieving a certain service from the network may no
longer be valid and an error message is returned to the
user. Obviously, it is thus desirable to avoid the broken
15 links, in order to be able to retrieve information about
an object without fail.

[Summary of the Invention]

20 It is therefore object of the invention to provide a
system and method capable of communicating information
associated with an arbitrary number of objects.

This object of the invention is solved by independent
25 claims 1 and 15 of the invention.

The invention advantageously allows to link an arbitrary
number of objects of the real world to information
services stored on an arbitrary number of data processing
30 units or application servers, which may be located at
arbitrary places. These services may be text, images,
application programs or any other kind of messages. The
data processing units or application servers preferably
store a plurality of application data packets comprising
35 data related to the services. Each of the plurality of
application data packets may be associated with one of the

plurality of objects of the real world, i.e., it contains information related to the object. The application data packets may be of arbitrary size.

5 Advantageously, each of a plurality of directory servers stores part of an arbitrarily scaleable data base containing object data associating each of the objects with at least one of the application data packets. The plurality of directory servers serve as key resource in
10 retrieving an application data packet related to an object. Means for receiving a read object tag from a reading means and for identifying the directory server for storing object data related to the read object tag and retrieving the object data are provided. During operation,
15 a system kernel receives data of an object tag associated to one of the plurality of objects, and based on a search performed by at least one of the plurality of directory servers, obtains the address of a storage location or locations, i.e., the address of application servers
20 storing application data packets related to the object. Subsequently the application data packets may be retrieved and can be supplied to a device. The device may be a mobile telephone or a data processing unit or the like. Alternatively, object data related to the read object tag
25 can be transmitted to the device. The invention thus advantageously allows to connect different services from different providers.

In an advantageous embodiment of the invention each of the
30 plurality of directory servers comprises tag memory means storing information about which of the plurality application data packets is associated with particular ones of the plurality of objects. Thus, a tag data block advantageously may comprise at least one object tag and at
35 least one application identifier. Also, tag data blocks may comprise addresses of application servers storing

application data packets corresponding to the application identifiers.

Each of the directory servers may advantageously also
5 comprise address memory means for storing address data blocks including information about application server addresses storing the application data packets specified in the tag memory means. An address data block may advantageously be provided for each application data
10 packet. Thus, an address data block may store an application identifier and the application server address of the server storing the corresponding application data packet. Address data blocks may also store object tags of objects associated to an application data packet. The
15 address data blocks may advantageously be used for removing application identifiers from object data, if corresponding application data packets are removed.

Tag memory means and address memory means advantageously
20 allow to solve the problem of broken links, since an object, via its tag, can indirectly be linked to particular storage locations, i.e., addresses of specific application servers. A look-up of a specific application data packet related to a particular object may therefore
25 advantageously be performed by searching for a specific object tag in the tag memory means and subsequently, application server addresses for respective application identifiers may be retrieved from the address memory means.

30 In another embodiment of the invention the system advantageously comprises memory means for storing a list of available directory servers in a hashtable and a hashfunction is provided for identifying a particular one
35 of the directory servers for storing information related to a specific object based on the hashtable. The

hashfunction is thus used for mapping all object tags onto the plurality of directory servers. The hashfunction can be used in operations for storing and removing one of the object tags and associated object data, retrieving object data related to one of the object tag from one of the directory servers, and relocating object data from one of the directory servers to another.

Advantageously, all object tags and directory server addresses may be numbered in an ascending order, tag data blocks of object tags with sequential numbers are stored on directory servers with sequential numbers and the list of all available directory servers, i.e., their addresses, sorted by assigned numbers, are maintained as the hashtable. Thus, the directory server storing information related to a particular one of the objects can be identified by the hashfunction. The determined directory server is likely to store object data related to the object tag. If it does not store the object data, the output range of the hashfunction can be halved.

If an object is to be inserted into data base of object data, the appropriate directory server can advantageously be computed using the hashfunction. Further, if a new directory server becomes available and is inserted into the hashtable, storing locations of application data blocks may advantageously be recomputed using the hashfunction.

Preferably, the hashtable is stored by at least one supervisor server, however, any other component of the system kernel may store the hashtable or a copy of the hashtable. It is thus possible that copies of the hashtable are stored on the directory servers, etc. The copies of the hashtable may advantageously be updated only periodically, in order to reduce processing time.

Providing copies of the hashtable at a plurality of devices of the system further reduces the response time of the system, since look up operations can be performed by many devices.

5

Further, a plurality of broker servers may be provided for storing information about components of the system kernel. The broker servers may also store copies of the hashtable.

10 Advantageously, retrieved application data packets may be communicated via fixed and wireless communication links to a mobile telephone or to a data processing device, used for playback or display of information. Data conversions, such as speech processing, can advantageously be performed
15 by specifically provided resource means.

Further, in order to provide a robust system, components of the system kernel can be replicated by replication components.

20

Still further advantages of the invention are described in dependent claims.

[Brief Descriptions of the Figures]

25

The invention can be more fully understood, if it is seen in conjunction with the accompanying drawing, wherein;

30

Fig. 1 shows a block diagram of an embodiment of the invention;

Fig. 2 illustrates an embodiment of the hashtable used to perform a lookup operation for identifying a particular one of the directory servers;

35

Fig. 2a shows a flow chart of steps performed in accordance with an embodiment of the invention for storing, retrieving and relocating object data associated with an object tag.

5

Fig. 3 shows a flow chart of steps performed in accordance with an embodiment of the invention for retrieving application data packets associated with an object;

10

Fig. 4 shows a flow chart of steps performed in accordance with an embodiment of the invention for identifying an directory server for storing new object data;

15

Fig. 5 shows a block diagram of an embodiment of the components of one of the plurality of directory servers as well as components of a tag data block and address data block, respectively;

20

Fig. 6 shows an embodiment of the system kernel;

Fig. 7 shows an embodiment of the system according to the invention including the Internet;

25

Fig. 8 schematically illustrates an embodiment of steps for performing the method according to the invention;

30

Fig. 9 schematically shows an embodiment of steps for performing the method according to the invention, including the Internet;

Fig. 10 shows another embodiment of steps for performing the method according to the invention, the steps

35

including lookup procedures performed by broker servers; and

Fig. 11 shows another example of steps for performing the method according to the invention including data conversions performed by resource means;

[Detailed Description of Embodiments]

10 In the following, preferred embodiments of the invention are described with respect to the figures.

Fig. 1 shows a block diagram of an embodiment of the system according to the invention. The system is arranged to link each of a plurality of objects with corresponding ones of a plurality of information services.

The embodiment of Fig. 1 comprises a system kernel K with at least one application server AS; AS1 - ASr and a plurality of directory servers DS; DS1 - DSn. The system kernel K is arranged to communicate data between a plurality of application servers and a telephone M, a data processing unit DPU or the like. The application servers each have an address IS; IS1-ISp and store a plurality of application data packets, each having an application identifier AI1 - AIm. The application servers may be part of a known datacom- or telecom network, such as the Internet. A plurality of objects D is marked with a plurality of tags T, one each is shown. A reader R is provided for reading data of an object tag and transmitting same the system kernel K.

The system is arranged to link the plurality of objects, which can, for example, be any products or items of the physical world to various kinds of information related to the objects. It is thus possible to associate each

specific one of the objects to a focused set of information services. A user may retrieve such a set of information services related to a particular one of the objects D or information about the information services by
5 reading the object tag T; T1- Tw using the reader R. The information about the object is then automatically obtained by the system kernel K from a corresponding one of the application servers. Obtained information may be sent from the system kernel to the telephone M, which may
10 be a regular telephone or a mobile telephone, or to the data processing unit DPU.

With the system according to the invention, the user is, e.g., able to access default information related to an
15 object or a group of objects, for example, as provided by the manufacturer of the particular objects or products. Further, the user can execute a specific service related to the object. The user can also look up services available for an object, for example a list of services
20 associated with the object and may browse the list. In this case a list of all services associated with the object can, e.g., be displayed on the display of the data processing unit DPU operated by the user. The system may also be used to automatically read object tags, e.g.,
25 within a room or passing a door or the like.

The plurality of application servers with the addresses IS; IS1-ISp and storing data related to the objects D may be placed at arbitrary locations in the world, similar to
30 today's computer networks, such as intranets, company networks or the Internet. It is also possible that part or all of the plurality of application servers constitute part of at least one known datacom- or telecom network and that the system kernel K only serves as a link between
35 objects and services. The application servers thus may be dedicated devices or shared with other networks. Data

stored on the application servers can, for example, be text, such as a user manual of a product, links to other servers storing related data or other kind of written information. Further, the data can comprise images, video, audio signals and the like. It is also possible that the exchange of data via the system kernel K between application servers and the mobile telephone and/or data processing unit includes an interactive execution of an application.

The reader R is arranged to read one of a plurality of object tags T; T₁ - T_w. The reader may be a bar code reader or any other reading device. The object tags can be active or passive tags, as commonly used and preferably are very small. Tags in the mm range are available today.

The reader R may be an independent device (PCMCIA size), connected to the mobile telephone M and/or data processing unit DPU, or may be integrated into the mobile telephone M and/or data processing unit DPU, as indicated in Fig. 1 by a broken line enclosing the reader, the mobile telephone M, the data processing unit DPU. For reading an object tag, a user preferably directs the reader at an object tag and initiates the reading process. It is, however, also possible, that object tags are read automatically, e.g., if in the vicinity of the reader.

The transmission of information between the reader R, the mobile telephone M and the data processing unit DPU and the system kernel K may be performed via wireless communication or via fixed communication lines. For example, data transmission may include a mobile telephone network, a telephone networks using fixed lines and computer networks.

Even though Fig. 1 only shows one reader R, the system is able to serve a large number of users operating a large number of readers. A user can be located anywhere, the only requirement is that the user connects to the system kernel for issuing a request for information and transmitting a read object tag. Preferably each user is also equipped with a device for receiving information retrieved from one of the application servers or directory servers which, e.g., may be the mobile telephone M or the data processing unit DPU.

In operation, the system kernel K receives a request for information from a user containing the object tag T; T₁ - T_w of an object D read by the reader R. Upon reception of the request, the system kernel K performs operations to identify application servers storing information related to the object D. Once the application servers and the addresses IS; IS₁ - IS_p, respectively, are appropriately identified, data associated with the object D can be retrieved from the application server and supplied to the user.

Since the amounts of data handled by the system, i.e., the number of objects and the number of application data packets may be extremely large, a single unit can not handle all information associating objects with application data packets. Therefore, the system kernel K includes the plurality of the directory servers DS; DS₁ - DS_m, each storing part of a data base of object data associating each of the application data packets with at least one of the plurality of objects.

It is preferred, that means are provided maintain information about available kernel components. In general, the information may be kept in any component of the system kernel. However, it is also possible, to provide one or a

plurality of dedicated supervisor servers (not shown) for this purpose. The number of supervisor servers may, e.g., depend on traffic handled by the system. The supervisor server / servers may, e.g., maintain an always up to date
5 list of addresses of all directory servers. In addition, periodically updated copies of the list may be stored elsewhere in the system kernel.

It is a key aspect of the invention that the data base of
10 object data is distributed over a plurality of directory servers DS; DS1 - DSn, allowing that the number of objects can be scaled almost arbitrarily by adding new directory servers to the existing ones for storing new object data. Each of the directory servers DS; DS1 - DSn preferably
15 stores object data related to a small number of the range of available object tags T; T1 - Tw. As mentioned above, object data related to an object tag preferably includes application identifiers AI1 - AI_m of application data packets related to the object as well as information about
20 storage locations of the application data packets, e.g., the addresses of application servers IS; IS1 - IS_p storing the application data packets.

According to an embodiment of the invention, the retrieval
25 of application data packets by the system kernel K can be performed in two steps. In a first step the directory server storing object data related to an object is identified and the object data is retrieved. In a second step, using the object data, application data packets are
30 retrieved from application servers and/or the object data or parts thereof are transmitted to the user, i.e., to the mobile telephone M and/or the data processing unit DPU.

The first step of identifying the correct directory server
35 may be performed via a look up in a hashtable H containing addresses or identifiers of all available directory

servers DS1 - DS_n. To facilitate this look up procedure, a hashfunction is used.

The hashfunction is used to map the plurality of objects
5 onto the plurality of directory servers DS; DS1 - DS_n.
Since the number of objects will be larger than the number
of directory servers, the hashfunction is used to assign
object data related to a group of objects to each of the
directory servers. Thus, each of the object tags is
10 assigned to a target directory server using the
hashfunction. Preferably, the hashfunction distributes
the object tags evenly over the available directory
servers. To facilitate such mapping, preferably a sequence
of all objects and directory servers is defined, e.g., by
15 numbers, strings or the like. Many different mapping
schemes or hashfunctions can be employed.

Since the distribution of object data over the plurality
of directory servers thus follows a defined scheme
20 corresponding to the hashfunction, it is possible to use
the same scheme for identifying the target directory
server storing object data related to a particular object
tag. If the object data should not be found on the target
directory server due to changes to the data base, the
25 hashfunction includes further steps to identify the actual
directory server storing the object data, as outlined with
respect to further embodiments.

The hashfunction can also be employed, if new object data
30 is to be inserted into the data base on the directory
server, if data has to be relocated or when the number of
directory servers changed, as outlined later in more
detail.

35 The system kernel K of the described embodiment comprises
at least one access server AS; AS1 - AS_r, which preferably

is responsible for receiving a request for information about an object including an object tag T; T₁- T_w read by the reader R. Further, preferably the at least one access server AS; AS₁ - AS_r is responsible for retrieving
5 addresses IS; IS₁ - IS_p of application servers obtained from at least one of the directory servers DS; DS₁ - DS_n and/or retrieving corresponding application data packets. In the embodiment of Fig. 1, the at least one access server AS; AS₁ - AS_r executes the chain of requests
10 connected to retrieving information from the system with respect to the object tag T; T₁- T_w read using the reader R.

In other embodiments, a plurality of arbitrarily located
15 access servers AS; AS₁ - AS_r may be provided, each serving a group of users, e.g., grouped by geographic location, or serving a subgroup of the plurality of objects.

After receiving a request for information including the
20 object tag T, the access server AS; AS₁ - AS_r performs operations to identify the directory server DS; DS₁ - DS_n storing information concerning application data packets related to the object.

25 This preferably includes sending the request including the object tag T; T₁- T_w to one of the directory servers DS₁; DS₂; ...; DS_n, which in turn, using the hashfunction and hashtable H, determines the directory server for storing the object tag T; T₁- T_w and forwards the request to that
30 particular directory server. However, it is also possible, that the access server AS; AS₁ - AS_r or other components of the system kernel K perform steps for identifying the correct directory server.

35 After identification of the correct directory server DS; DS₁ - DS_n, the request, including the object tag T; T₁ -

Tw, is forwarded to the identified directory server. The directory server, in a subsequent step, performs operations to determine all addresses of application servers IS; IS1 - ISp storing application data packets associated with the read object tag T; T1- Tw and thus object D. Intermediate steps are possible, where the look up request is relayed to further devices before it reaches the correct directory server, as outlined later.

10 The obtained addresses IS; IS1 - ISp and optionally other information can be returned to the access server AS; AS1 - ASr, which in the following retrieves the specified application data packets from the identified application servers or transmits the addresses IS; IS1 - ISp and possibly other information directly to the user, i.e., the mobile telephone M or the data processing unit DPU.

As noted before, the application servers provide various services associated to physical objects. However, the system according to the invention is preferably compatible with other information systems, in order to include additional information services. A compatible system can, for example, be the Internet. In this case WWW information could be retrieved based on an object tag by the system according to the invention. It is also possible, that the system entirely uses storage means of existing computer networks, such as the Internet, and does not provide application servers of its own. It is further possible, that the system and method according to the invention use standard and/or amended protocols of a known datacom- or telecom network for retrieving information associated with an object.

In the following, with respect to Fig. 2, an embodiment of a list of available directory servers DS; DS1 - DSn, maintained in the hashtable H, is described.

As outlined above, after receiving an object tag T; T1 - Tw from the reader R, the access server AS; AS1 - ASr transmits the request to one of the directory servers, which in turn performs an operation to identify the particular one of the plurality of directory servers DS; DS1 - DSn for storing object data related to the received object tag T.

10 The hashtable may be stored by any component of the system kernel K. However, preferably, an always up to date hashtable for keeping track of newly available directory servers and of removed directory servers is stored in at least one supervisor server HS1 - HSt. Copies of the
15 hashtable may additionally be stored in each of the directory servers for performing look up operations upon receiving a request regarding the correct directory server. Further, copies of the hashtable can be stored in the at least one access server or broker servers, not
20 shown.

The copies of the hashtable do not necessarily have to be always up to date. They are preferably updated only periodically by updating means, also not shown. Since the
25 look up of object data is a non-critical step, resources can be saved by only periodically updating the copies of the hashtable H.

As briefly outlined with respect to Fig. 1, it is preferred, that one of the directory servers DS1; DS2; ...; DSn identifies the directory servers storing information related to a requested object tag. However, other components of the system kernel K may serve as means for identifying the correct directory servers.

35

Preferably, the hashtable H comprises a number of entries for storing records including addresses of application servers.

- 5 In the example of Fig. 2 the hashtable comprises 8 entries, addresses of available servers are stored as records in respective sequential entries of the hashtable. Thus, the hashtable constitutes an ordered list of all available directory servers, as shown in Fig. 2. The records stored in the hashtable H are indicated by A, B, C and D stand for addresses of four directory servers DS; DS1 - DSn. However, any other order is possible, e.g., D, E, A, C.
- 10
- 15 To avoid unnecessary look up operations for object tags at directory servers, as outlined above, it is preferred that object data is stored on directory servers according to the hashfunction, which may be executed by search means SM indicated in Fig. 2. The search means SM groups object tags, preferably in correspondence with the number of objects and the number of available directory servers, i.e., a target directory server for storing as well as for retrieving object data is determined based on an identifier of an object tag, which, e.g., may be a number assigned to the tag, and the number of available directory servers DS; DS1 - DSn.
- 20
- 25

The object tags may be grouped and object data related to each group of object tags may be stored on one of the plurality of directory servers using hashfunction or any scheme. It only needs to be assured that for storing object data related to objects on the directory servers and for determining the correct directory server upon receiving a request for information concerning an object, the same scheme or hashfunction is used. For example, as a storage scheme, all object tags and directory servers

30

35

could be numbered sequentially and object data related to object tags with sequential numbers may be stored directory servers with sequential numbers.

5 In the shown embodiment, a hashfunction is used, which maps object tags with sequential numbers onto directory servers with sequential numbers. Thus, each of the directory servers DS; DS1 - DS_n stores a subgroup of sequentially numbered object tags T1 - T_w, whereby object
10 tags with sequential numbers are stored on directory servers with sequential numbers. Accordingly, object data related to the first object tag T1 is stored on the first directory server DS1, object data related to the second object tag T2 is stored on the second directory server
15 DS2, object data related to the third object tag T3 is stored on the third directory server DS3 and object data related to the fourth object tag T4 is stored on the fourth directory server DS4. Since 4 directory servers are available, object data related to the fifth object tag T5
20 is again stored on the first directory server DS1 and likewise all other object tags are stored on the available four directory servers.

The above hashfunction for storing/retrieving object data
25 on directory servers only serves as an example, other mapping schemes may be used. For example, it is also possible, that blocks of object tags with numbers in certain ranges could be stored on a particular directory servers.

30

An important feature of the system is the ability to handle a large data base of object data. Further, the system provides features to adapt to a varying size of the data base of object data. Specifically, the system is able
35 to handle the insertion of new object data or removal of obsolete object data. Also, in case the capacity of the

system needs to be increased, new directory servers can be added and storage locations of object data can be rearranged accordingly. Similarly, directory servers may be removed. All of this is accomplished by suitably
5 arranging the hashtable H and suitably assigning directory servers for object data using the hashfunction.

In the following, an example of processing steps for maintaining the hashtable H and data base of object data
10 up to date and steps for retrieving object data are described with respect to Fig. 2a.

First, some maintenance operations are briefly outlined in general.

15

If a new directory server becomes available, it may be added to the hashtable H as a new record. Analogously, one of the directory servers could be removed, in which case one of the hashtable entries becomes vacant.

20

However, in the case the number of available directory servers changed, previously stored object data was mapped onto the plurality of directory servers using a hashfunction based on the previous number of directory
25 servers, whereas a target directory server is now identified based on a new number of directory servers. This will sometimes not lead to the directory server actually storing object data related to the desired object. In this case the hashfunction may be designed to
30 interrogate the remaining directory servers according to a specific sequence until the directory server actually storing the desired object data has finally been identified.

35 In the above case it is now preferred that the previously stored object data is transferred to the correct target

directory server, i.e., the directory server which was determined based on the current, that is, new number of directory servers. The transfer can, e.g., be carried out, if upon a request object data are found not to be located
5 at the correct directory server.

According to this proceeding, after the number of directory server changed, the data base of object data is gradually updated with respect to correct storage
10 locations of object tags and associated object data, i.e., are moved to their respective target directory servers.

It is noted, that a newly available directory server may also be inserted as a backup server to replicate one of
15 the directory servers, in which case that part of the data base of object data is copied from the replicated server to the backup server.

The above maintenance steps are preferably executed by the
20 at least one supervisor server HS1 - HSt, in order to always use an up to date hashtable.

In the following, the steps of the flow chart of Figure 2a described in detail.

25

Initially, the insertion of a new object data corresponding to a new object tag is described.

In a step S21 the system is advised to insert new object
30 data into its data base distributed on the plurality of the directory servers.

In a step S22 the primary directory server for storing the new object data is computed based on, e.g. a number
35 assigned to the new object tag as well as based on the number of available directory servers. The step of

identifying the primary directory server is preferably performed by one of at least one supervisor servers HS1 - HSt. However, any other component of the system kernel K could identify the primary directory server. The
5 hashfunction for identifying the primary directory server for storing the new object data therefore depends on the number of available directory servers and the target directory server for a particular object tag therefore varies with the number of available directory servers, as
10 indicated by the double arrow in Fig. 2a.

After the target directory server for the new object data has been identified using the hashfunction, the object data is transferred to the target directory server and
15 stored thereon in a step S23. This completes the sequence of steps for inserting new object data.

In the following, also with respect to Figure 2a, steps for performing a lookup operation for object data related
20 to a desired object tag or object is described.

In a step S24 a lookup request is received by the system kernel K. As it has been outlined before, the request usually is issued by a user reading an object tag using
25 the reader R.

Following the reception of a lookup request, the primary directory server for the particular object tag is determined according to the hashfunction in step S22. It
30 is noted that step S22 is identical for inserting data and retrieving object data, as indicated by the box with broken lines. After the primary directory server for the object tag has been determined using the hashfunction, a request for object data is transmitted to the target
35 directory server in a step S25.

In a step S26, at the primary directory server, it is determined, whether the object data associated with the object tag is actually located at the primary directory server. As outlined before, this is not always the case, since the data base varies in size and directory servers may be added or removed. Therefore, in case a new directory server has been added after object data related to the desired object has been stored on the data base, the primary directory server computed in step S22 will differ from the directory server, where the object data is actually stored. The same holds true, if one of the directory servers has been removed after object data related to the object tag has been inserted into the data base.

If the object data is located on the identified primary directory server, in a step S27 the object data is retrieved from the directory server and subsequently steps for providing the user with desired information are performed by the system kernel are carried out. As outlined before, this may include retrieving application data packets from application servers based on the object data or directly transmitting object data or parts thereof to the user, i.e., to the data processing unit DPU and/or mobile telephone M.

If in step S26 it has been determined that object data related to the object tag is not located at the identified primary directory server, in a step S28, the lookup request is forwarded to other directory servers. In case the number of directory servers has been increased recently, the lookup request may be forwarded to a directory server which is determined using the hashfunction based on a previous number of available directory servers. The same holds true, if the number of directory servers has been decreased recently. If none of

the directory stores the desired object data, an error message is generated and the operation ends.

However, it is also possible, that the lookup request is forwarded to all remaining directory servers. If the object data was not located at the desired location, after the correct directory server has been identified in step S28, in a step S29 the object data is retrieved from the directory server and erased from its data base.

Following, the flow advances to step S23. In step S23, as outlined before, the retrieved object data is stored on the target directory server, determined in step S22.

Fig. 3 describes steps for retrieving application data packets related to an object using a flow chart according to another example of the invention. In this embodiment look up operations are described involving a hashfunction employing a modulo operation for identifying a directory server. Fig. 3 also describes, how object data can be rearranged using the hashfunction, in case it is detected that the object data is not stored on the correct directory server.

In a step S31 the system kernel K receives a request from a user, requesting information related to an object. A request at least includes an object tag T; T1 - Tw of an object D transmitted from the reading means R to the system kernel. Additionally, the request may, e.g., include an address or identifier of an user and parameters specifying the type of information or service requested. Preferably, the request is received by one of the access servers AS; AS1 - ASr. However, as mentioned before, other components of the system may also receive or process the request.

Upon reception of the request for information related to an object, in a step S32, the number of entries in the server hashtable H is assigned to a parameter α and the number of the object tag is assigned to a parameter β . In
5 the following step S33 a modulo operation $\beta \bmod \alpha$ is carried out and the result is assigned to a parameter γ .

In the subsequent step S34 it is determined, whether the hashtable location with the number γ contains a record
10 comprising an address of one of the directory servers DS; DS1 - DS_n or not, i.e., it is determined, whether a directory server with the assigned number γ is available.

If the location γ of the server hashtable is empty, in a
15 step S35 an operation $\alpha = \alpha/2$ is performed and the flow returns to step S33. In S33, again, $\beta \bmod \alpha$ is computed in order to obtain a new γ . The flow then again reaches step S34 and once again it is determined, whether the hashtable location γ contains a record comprising one of the
20 directory server addresses.

This loop of steps S33, S34 and S35 is repeated until, in step S35 it is determined that the hashtable location γ contains a record comprising a directory server address.
25 Then, in a step S36 a request including the read object tag is transmitted to the target directory server, i.e., the directory server, whose address is stored at the hashtable location γ .

30 Subsequently, in a step S37, the target directory server determines, whether the object data stored thereon actually includes a record comprising the read object tag. In case such a record can not be found, the flow returns to step S33, and γ is newly computed. The flow then

continues as outlined before, until the directory server storing the object data is found. If none of the directory servers stores the object data, an error message is generated.

5

In the step S38, an object data relocation is performed, if the first available directory server, computed by the above method, did not contain object data comprising the read object tag. In this case, the object data is

10 relocated to the first available directory server, as computed with the above method. The relocation operation preferably includes storing the object data on the "new" directory server and deleting the object data on the "old" directory server.

15

In a step S39 the directory server storing the object data determines from the object data application server addresses IS; IS1 - ISp, storing application data packets associated with the object and returns retrieved addresses

20 and application identifiers to the access server AS; AS1 - ASr.

In a step S40 respective data packets are retrieved, using the obtained addresses of application servers or the

25 application server address is transmitted to the user.

In other embodiments, the number of the location of the hashtable including the address of a directory server storing desired object data may be obtained by computing

30 the number of the target object modulo the number of directory servers. Also, it may be adhered to a different sequence of steps for performing the look up operation, e.g., a sequence of steps S39, S38 and S40.

35 It is also noted that in other embodiments, instead of retrieving application data packets, the address

information and further information about services may be transmitted to, e.g., the unit initiating the request.

Further, instead of a modulo operation, other mathematical operations providing an analogous distribution of object
5 data onto the plurality of directory servers DS; DS1 - DS_n may be employed.

In the following an example of operations for entering object data related to a new object into the data base
10 maintained on the plurality of directory servers DS; DS1 - DS_n is described with respect to Figure 4. In Fig. 4, the hashfunction explained with respect to Fig. 3 is used.

It is preferred, that for inserting object data into the
15 data base, the always up to date hashtable stored in the at least one supervisor server HS1 - HS_t is used.

In a step S41 the system kernel K receives a request from a user or system-administrator, to insert object data
20 related to a new object into the data base maintained on the plurality of directory servers.

In steps S42 to steps S45, analogously to Figure 3, the number γ of the directory server for storing the object
25 data is computed. Since steps S42-S45 correspond to steps S32-S35, a description thereof is omitted.

If in step S44 it is determined that a directory server at location γ is available, in a step S46 the object data is
30 stored on the directory server at location γ .

Depending on the hashtable, in step S44 a directory server at location γ of the hashtable will be identified. In the following, in a step S47 the system kernel will initiate

the storage of the object data related to the new object tag at the directory server γ .

Although not described, the above operation may also
5 include storing respective application data packets on application servers.

Analogously to the previous example described with respect to Figure 3, in other embodiments the target directory
10 server for storing object data related to a new object tag can be obtained by applying the hashfunction on the available number of directory servers.

The steps described above with respect to Figure 3 and
15 Figure 4 assure that object data related to an object tag is most likely stored on a directory server at location γ of the hashtable. Moreover it is assured, e.g., if a new directory server has been inserted or an old one has been removed that object data is rearranged appropriately.

20

In the following, with respect to Fig. 5, an embodiment of one of the plurality of directory servers DS; DS1 - DS_n is described.

25 As an example, components of the directory server DS1 are illustrated. The directory server DS1 comprises a central processing unit CPU for controlling operations of the directory server. Further, tag memory means TM are provided, for storing a plurality of tag data blocks TB1-
30 TB_i, each comprising at least one of the object tags T; T1 - T_w identifying an object and at least one of the application identifiers AI1-AI_m. Additionally, the tag data blocks can comprise application server addresses IS; IS1 - IS_p, storing application data packets corresponding
35 to the at least one application identifiers AI1 - AI_m.

The embodiment of directory server DS1 shown in Fig. 5 further comprises address memory means AM for storing a plurality of address data blocks AB1-ABk, each comprising one of the application identifiers AI1 - AI_m, the corresponding application server address IS; IS1 - IS_p and, optionally, corresponding object tags T; T1 - T_w. The address data blocks can be used to perform garbage collection, e.g., if an application data packet has been removed. In this case, the address data block allows to identify tag data blocks storing the respective application identifier.

On the right side of Fig. 5 an example of a tag data block TB_i is illustrated. At a first storage location of the data block an object tag is stored, and at subsequent locations of the tag data block application identifiers of application data packets related to the object tag T; T1-T_w are stored. In the shown case, application identifiers AI10 and AI12 are included into the tag data block TB_i. Additionally, as indicated by broken lines, the tag data block TB_i may comprise application server addresses, of which the application server address IS2 is shown, assumed to store application data packets corresponding to the application identifiers AI10 and AI12.

Also on the right side of Fig. 5, an example of an address data block AB_k is shown. At a first location of the address data block AB_k an application identifier is stored. In the shown case, the application identifier AI10 is stored. At a subsequent location of the address data block AB_k the application server address IS2 is stored, since in the embodiment of Fig. 5 it is assumed that application data packet with the application identifier AI10 is located on application server with the address IS2. Additionally, as indicated by broken lines, the

address data block AB_i may include object tags, of which the object tag T; T₁- T_w is shown, corresponding to the application data packet AI₁₀.

- 5 In alternate embodiments, the directory server may comprise single memory means, in which case all object data related to an object are stored in the provided memory means.
- 10 If the directory server DS₁ receives a lookup request for a specific object, it is first determined, whether the object is actually located on the directory server DS₁. If it is not located on the directory server, the request containing the object tag may be forwarded to other
- 15 directory servers. However, in case a tag data block containing the object tag is stored on directory server DS₁, operations are performed to retrieve information about the location of application data packages associated with the object. In the embodiment of Fig. 5, if
- 20 information concerning an object tag T; T₁- T_w is requested, the directory server DS₁ will identify tag data block TB_i. Tag data block TB_i includes application identifier AI₁₀ and the application server address IS₂.
- 25 If the application server address IS₂ is not included in the data block, it will be determined from address data block AB_k. A plurality of such lookup procedures regarding a plurality of application data packets can be performed by the directory server and all results will be returned
- 30 to the unit, which issued the search request.

In the following, an embodiment of the structure of an object tag is briefly described. In order to be able to reference a sufficiently large number of objects, an

35 object tag preferably contains at least 128 bits. The bits

may code digits or signs according to the ASCII code or the like.

As an example, in the following a case is described, where
5 digits are coded. The object tag is preferably constituted by a general part and a specific part. For example, if a certain provider requests a number series of 100,000 object tags, for instance, the number series 5878700000-5878799999 might be reserved. In this case, series data
10 can be stored using an identification number 5878700000. The most significant digit of an object tag preferably describes the length of the general part of the object tag, in the above case 5 digits. When a lookup of general information is performed for an object tag in this series,
15 for instance tag 5878701234, the object tag is identified as being part of the above number series of 100,000 numbers by the leading 5 digits. The series is then constructed by letting the five last digits to zero and the lookup is then performed with the series number
20 5878700000.

The above example shows only object tags with ten digits, in the real system, however, preferably much larger numbers of digits are used.

25

In the following, an embodiment of the system kernel K is described with respect to Fig. 6.

The system kernel of the shown embodiment of Fig. 6
30 comprises an arbitrary number of access servers AS; AS1-ASr and directory servers DS1-DSn, an arbitrary number of broker servers BS; BS1-BSs and resource means RS1-RSu and supervisor servers HS1 - HSt. All components are connected via a network N for communication with each other. In
35 order to provide a robust system, all or some of the

access servers, broker servers, directory servers or other components of the system kernel may be replicated.

The access servers AS; AS1-ASr constitute the link between
5 the user and the system kernel. For example, if a user
wishes to obtain information about a certain object, the
object tag is read using a reader and transmitted to one
of the access server AS; AS1-ASr, preferably an access
server located nearby. The access server could be, for
10 example, accessed by connecting a mobile device to a
network node of a mobile communication network, which
would transmit a lookup request to an appropriate access
server. Besides being responsible for receiving an object
tag from the outside world, the access servers AS; AS1-ASr
15 preferably also supervise the entire lookup operation of
the system for retrieving and presenting information
related to an object. Lookup operations under control of
the access servers using the directory servers have
previously been described with respect to Figures 1 to 4.

20 The broker servers BS; BS1-BSs are responsible for
maintaining a data base of directories, resources and
other brokers connected to the network. Therefore, the
broker servers each preferably comprise memory means for
25 storing a list of directory server addresses, as well as
for storing addresses of resource means and addresses of
other broker servers. Upon reception of a request for
information related to an object, an access server can use
at least one of the broker servers for performing certain
30 lookup operations with respect to suitable directory
server addresses, resource means, etc. In some cases, the
broker servers may also perform steps to identify an
appropriate one of the directory servers.

35 The resource means RS1-RSu are provided for performing
certain operations on application data packets, for

example speech rendering, speech recognition and language translation services, in order to reduce the complexity of application implementation.

- 5 The supervisor servers HS1 - HSt preferably maintain an always up to date hashtable used for insert and/or remove of object data.

The system kernel K is preferably distributed, possibly
10 world-wide. Its components can be connected by telecommunication networks or by existing computer networks, such as the Internet.

In the following, another embodiment of the invention is
15 described with respect to Figure 7. Figure 7 shows one of a plurality of objects D, marked by an object tag T, reading means R connected to a mobile telephone M or a data processing unit DPU, the system kernel K, as described previously as well as application servers IS;
20 IS1-ISp connected to the system kernel K via the Internet.

The operation of the system according to Figure 7 is as follows. An object tag T; T1- Tw read by the reader R is transmitted via fixed communication lines or wireless
25 communication links to the system kernel K. The system kernel K performs a lookup operation to retrieve information about the exact location of application data packets containing information related to the object D associated with the object tag T. Once the system kernel K
30 has successfully retrieved the information, preferably addresses of application servers storing information related to the object, the information about storage locations is directly presented to a user or the system kernel may retrieve the information from the application
35 servers which then may be transmitted to the user via the mobile telephone M or the data processing unit PDU.

Figs. 8 to 11 schematically illustrate steps of an example for performing the method according to the invention.

- 5 Firstly, with respect to Fig. 8, an example of steps for retrieving information related to an object are described.

In a first step S81 the mobile station M or the data processing unit DPU issues a lookup request for
10 information related to an object, that is, an object tag read by the reader R. The lookup request is transmitted to the access server AS; AS1 - ASr. The access server then transmits the request to one of the directory server which in turn identifies the correct directory servers DS; DS1 -
15 DSn storing object data related to the read object tag. However, in other embodiments the identifying of the correct directory server may also be performed by the access server. Examples of steps of identifying the correct directory servers have been outlined previously,
20 specifically with respect to Fig. 3.

In a second step, S82, the access server AS; AS1 - ASr requests information from one of the directory servers concerning information related to the object tag. The
25 directory server will perform a lookup operations in its data base, e.g. using a copy of the hashtable, suitably forwards the request to the directory server storing the object data which will identify application data packets associated with the object as well as their respective
30 storage locations, i.e. addresses of application servers. The directory server transmits the data to the access server in a step S83.

Following, in steps S84 and S85, the access server AS; AS1
35 - ASr will either transmit the information retrieved from the directory servers to a user or will perform operations

for retrieving specific application data packets from the application servers. In a last step S86, the access server then presents retrieved data to the data processing unit DPU or the mobile telephone M of the user issuing the request for information.

A second example of the method according to the invention is described with respect to Fig. 9. The example of Fig. 9 is particularly useful, the system used in combination with a known datacom- or telecom network, such as the Internet. In this case, the system according to the invention will mainly be used for performing the lookup of a regular Internet address, such as a service via a HTTP request.

In a first step S91 the user via the data processing unit DPU or the mobile telephone M issues a lookup request which is received by the access server AS; AS1 - ASr, as outlined with respect to Figure 8. Analogous to steps S82 and S83 of Fig. 8, the access server AS; AS1 - ASr initiates operations for identifying a correct directory server and retrieving information related to the object tag which is basis of the lookup request in steps S92 and S93.

In a step S94, the access server can retrieve application data packets based on the look up result and transmit the result to the data processing unit DPU or mobile telephone M. Alternatively, the access server directly returns the lookup result to the data processing unit DPU or mobile telephone M, which subsequently, in a step S95 may be used for directly retrieving application data packets from an application server. The application data packets are received in a step S96. Alternatively, a regular Internet lookup, such as a regular HTTP request, may be performed in steps S95' and S96'.

Now, with respect to Fig. 10, an alternative example for identifying the correct directory server is described.

- 5 In a first step S101, analogously to the previous figures, a lookup request for information related to an object tag is received by the access server AS; AS1 - ASr.

Different from the previous examples, broker servers BS; BS1 - BSs are now used for assisting the access server AS; AS1 - ASr in performing the lookup operation to identify the correct directory server or to perform look ups of resources of the system. In a step S102 the access server requests directory assistance from the broker server BS; BS1 - BSs. In a step S103, the address of the correct directory server or resource of the system is transmitted by the broker server, and in steps S104 and S105 the access server retrieves object data related to the object tag, analogously to the previous figures.

20 Alternatively, in step 103 the broker server BS; BS1 - BSs may return the address of any other preferred directory server to the access server and the access server then forwards the look up request to the preferred directory server, which then identifies the correct directory server storing desired object data.

Another example of steps for performing the method according to the invention is described with respect to Figure 11. The embodiment of Figure 11 is, for example, suitable for applications where retrieved application data packets need further processing before being delivered to the user. As outlined before, the processing can be performed by the resource means RS; RS1-RSu, in order to reduce the processing load of the access server AS; AS1 - ASr or other servers involved.

As in the previous examples, in a step S111 a lookup request for information related to a particular object tag is received by the access server. Since the lookup of the correct directory server is the same as in previous examples, a description thereof is omitted. In steps S112. and S113, the access server AS; AS1 - ASr retrieves at least one application data packet from an corresponding one of the application servers and in a step S114 the at least one application data packet is transmitted to the resource means RS; RS1-RSu, which performs conversions on the received data and retransmits the data back to the access server in a step S115.

15 In a last step S116 the converted data is forwarded to the data processing unit DPU and/or the mobile telephone M.

Alternatively, as indicated by broken lines, instead of steps S113 - S116, in a step S113' application data packets may be directly transmitted from the application server to the resource means RS; RS1 - RSu, which perform the operations on the received data. Further the data may be directly transferred to the data processing unit DPU or the mobile telephone M in a step S115', instead of steps S115 and S116.

Claims

5 1. Communication system, comprising:

a plurality of objects (D) each identified by an object tag (T);

10 a plurality of application servers each having an address (IS; IS1 - ISp) and each comprising memory means for storing a plurality of application data packets, each related to one of the objects and identified by an application identifier (AI1 - AIm);

15

reading means (R) for reading one of the plurality of object tags (T);

a system kernel (K), comprising:

20

a plurality of directory servers (DS; DS1 - DSn) each having an address and comprising memory means (TM; AM) for storing in a distributed data base object data associating each of the objects with at least one of the application data packets;

25

means for receiving the read object tag (T) from the reading means (R) and means for identifying the directory server for storing object data related to the read object tag and retrieving the object data; and

30

means for retrieving at least one of the application data packets based on the object data or transmitting at least part of the object data to a receiving unit (M, DPU).

35

2. Communication system according to claim 1,
characterized in that

5 object data corresponding to an object comprise an object
tag, at least one application identifier and the address
of the at least one application server storing the at
least one application data packet identified by the at
least one application identifier.

10

3. Communication system according to claim 1 or 2,
characterized in that

each of the directory servers (DS; DS1 - DSn) comprises:

15

tag memory means (TM) for storing a plurality of tag data
blocks (TB1 - TBi), each comprising one of the object tags
(T) and at least one of the application identifiers (AI1 -
AI_m); and

20

address memory means (AM) for storing a plurality of
address data blocks (AB1 - AB_k), each comprising at least
one of the application identifiers and the address of the
application server storing the at least one of the
25 application data packets corresponding to the at least one
of the application identifiers.

4. Communication system according to one of the claims 1
to 3, characterized by

30

memory means for storing a list of all available directory
servers in a hashtable (H); and

means (DS; DS1-DSn; AS; AS1-AS_r), using a hashfunction for

35 identifying the directory server (DS; DS1 - DSn) for

storing the object data related to the read object tag,
based on the hashtable.

5. Communication system according to claim 4,
5 characterized by

at least one supervisor server (HS1 - HSt) for inserting
and removing object data from the data base distributed on
the plurality of directory servers using the hashfunction;
10 and

updating the hashtable (H), if the number of available
directory server changes.

15 6. Communication system according to claim 4 or 5,
characterized in that the plurality of directory servers
stores copies of the hashtable (H) to perform the step of
identifying the directory server (DS; DS1 - DSn) storing
the object data related to the read object tag using the
20 hashfunction.

7. Communication system according to one of the claims 4
to 6, characterized by updating means for periodically
updating the copies of the hashtable stored in the
25 directory servers.

8. Communication system according to one of the claims 1
to 7, characterized by a plurality of broker servers (BS;
BS1 - BSs) comprising memory means for storing addresses
30 of the directory servers, addresses of resource means (RS;
RS1 - RSu) and addresses of the broker servers.

9. Communication system according to one of the claims 1
to 8, characterized by a plurality of access servers (AS;
35 AS1 - ASr) handling communication between the plurality of

application servers and a mobile telephone (M) and/or data processing unit (DPU).

10. Communication system according to one of the claims 1
5 to 9, characterized in that the reading means (R) is
connected to the mobile telephone (M) or the data
processing unit (DPU), connected to the system kernel (K)
for a transmission of the read object tag (T) via a
wireless communication link or stationary communication
10 link.

11. Communication system according to one of the claims 1
to 10, characterized in that the resource means (RS; RS1 -
RSu) perform data conversions on the application data
15 packets obtained from the application servers.

12. Communication system according to one of the claims 1
to 11, characterized in that the system includes a known
datacom- or telecom network.

20

13. Communication system according to one of the claims 1
to 12, characterized in that components of the system
kernel (K) are replicated by replication components and/or
each of the application servers is replicated by a
25 replication application server.

14. Communication system according to one of the claims 1
to 13, characterized in that the object tags (T; T1 - Tw)
each comprise at least one general part and a specific
30 part.

15. Method of communicating information, comprising:

marking each of a plurality of objects with an object tag;

35

storing a plurality of application data packets, each identified by an application identifier, in memory means of a plurality of application servers, each identified by an application server address;

5

storing in each of a plurality of directory servers (DS; DS1 - DSn) part of a distributed data base of object data associating the plurality of objects with the plurality of application data packets;

10

reading one of the object tags using a reading means (R) and transmitting the read object tag to an access server (AS; AS 1 - ASr);

15 identifying the directory server (DS; DS1 - DSn) storing object data corresponding to the object tag;

obtaining the address of at least one of the application servers storing at least one of the application data packets associated with the object based on the object data; and

20

retrieving the at least one of the application data packets using the address or transmitting data corresponding to the address to a mobile telephone (M) and/or a data processing unit (DPU).

25

16. Method of communicating information according to claim 15, characterized in that

30

object data associated with an object comprise at least one object tag, at least one application identifier and the address of the at least one application server storing the at least one application data packet identified by the at least one application identifier.

35

17. Method of communicating information according to claim 15 or 16, characterized in that

the step of storing the object data comprises:

5

storing a plurality of tag data blocks, each comprising at least one of the object tags and at least one of the application identifiers;

10

storing a plurality of address data blocks, each comprising at least one of the application identifiers and the address of the application server storing the at least one application data packet corresponding to the at least one of the application

15

identifiers; and

the step of obtaining the address comprises a search step to obtain at least one of the address data blocks of the at least one application identifier of the tag data block containing the read object tag (T).

20

18. Method of communicating information according to claim 17, characterized in that the tag data block comprises addresses of the application servers storing the application data blocks associated with the object.

25

19. Method of communicating information according to one of the claims 15 to 18, characterized by

30

storing a list of all available directory servers in a hashtable;

mapping all object tags employing a hashfunction and the hashtable onto the directory servers.

35

20. Method of communicating information according to claim 19, characterized by

5 using the hashfunction in inserting and removing object data corresponding to one of the object tags from the data base;

retrieving object data related to one of the object tags from one of the directory servers; and

10

relocating object data related to one of the object tags from one of the directory servers to another.

21. Method of communicating information according to one 15 of the claims 19 or 20, characterized in that

the object tags and the directory server addresses are numbered in ascending order and object data corresponding to object tags with sequential numbers are stored on 20 directory servers with sequential numbers;

a list of directory server addresses, sorted by assigned numbers, is maintained as the hashtable; and

25 the hashfunction and the hashtable is used for identifying one of the directory servers.

22. Method of communicating information according to claim 21, characterized in that relocating object data related 30 to an object, if one of the directory servers is removed or an additional directory server is inserted into the hashtable, includes executing the hashfunction.

23. Method of communicating information according to claim 35 21 or 22, characterized in that inserting object data

related to a new object includes assigning a number to the new object tag and executing the hashfunction.

24. Method of communicating information according to one
5 of the claims 21 to 23,
characterized in that the hashfunction for identifying the
directory server includes determining the value of the
number of the object tag modulo the number of directory
servers or determining the value of the number of the
10 object tag modulo the number of hashtable records divided
by a multiple of two.

25. Method of communicating information according to one
of the claims 15 to 24, characterized in that the
15 identifying of the directory server is performed by one of
the directory servers or one of a plurality of broker
servers (BS; BS1 - BSs), arranged in a network.

26. Method of communicating information according to one
20 of the claims 15 to 25, characterized in that the
plurality directory servers and/or the plurality of broker
servers (BS; BS1 - BSs) maintain a copy of the hashtable
and the copies are periodically updated.

25 27. Method of communicating information according to one
of the claims 15 to 26, characterized in that

the application data packets include data and/or audio
signals containing information about the object or data
30 related to an execution of an application; and

the mobile telephone or the data processing unit is used
for control and display or play back of information
received with the application data packets.

35

28. Method of communicating information according to one of the claims 15 to 27, characterized in that the application data packets are processed by resource means (RS; RS1 - RSu).

5

29. Method of communicating information according to one of the claims 15 to 28, characterized in that the application servers constitute part of a known datacom- or telecom network.

10

30. Method of communicating information according to one of the claims 15 to 29, characterized in that the system is communicating over a known datacom- or telecom network and/or connects services provided by the known network.

15

31. Method of communicating information according to one of the claims 15 to 30, characterized in that components of the system kernel (K) are replicated by backup components.

FIG.1






FIG.2




3/10

FIG.2a




4/10

FIG.3



5/10

FIG.4



6/10

FIG.5





FIG.6



8/10




FIG.7

FIG.8





FIG.9



10/10

FIG.10





FIG.11



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 98/06752

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04L29/06 H04L29/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATANKAR A K ET AL: "A DIRECTORY SERVICE FOR A FEDERATION OF CIM DATABASES WITH MIGRATING OBJECTS" PROCEEDINGS OF THE TWELFTH INTERNATIONAL CONFERENCE ON DATA ENGINEERING, NEW ORLEANS, FEB. 26 - MAR. 1, 1996, no. CONF. 12, 26 February 1996, pages 142-150, XP000632590 SU S Y W (ED) see abstract see page 142, right-hand column, line 13 - page 145, left-hand column, line 22 see page 146, left-hand column, line 10 - line 37	1,3,4,6, 9,10,15, 17,19,20
Y		2,8,11, 12,14, 16,18, 25,26,29
A	-/--	7,13,

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

16 February 1999

Date of mailing of the international search report

25/02/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Poggio, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 98/06752

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p style="text-align: center;">---</p> <p>EBERHARDT R ET AL: "ELECTRONIC COMMERCE - A COMPARATIVE STUDY OF WEB BASED DATABASE ACCESS" ISS '97. WORLD TELECOMMUNICATIONS CONGRESS. (INTERNATIONAL SWITCHIN SYMPOSIUM), GLOBAL NETWORK EVOLUTION: CONVERGENCE OR COLLISION? TORONTO, SEPT. 21 - 26, 1997, vol. 2, 21 September 1997, pages 97-104, XP000704460 ABDALLAH ABI-AAD ET AL see abstract see paragraph 1 - paragraph 3</p>	<p>21-24</p> <p>8, 11, 12, 25, 26, 29</p>
A		5
Y	<p style="text-align: center;">---</p> <p>WO 89 02631 A (DIGITAL EQUIPMENT CORP) 23 March 1989 see abstract see page 3, line 1 - line 17 see page 4, line 19 - page 5, line 28 see figures 1,2</p>	<p>2, 14, 16, 18</p>
A	<p style="text-align: center;">---</p> <p>EP 0 624 964 A (PLESSEY TELECOMM) 17 November 1994</p> <p style="text-align: center;">-----</p>	<p>1, 11, 15</p>

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 98/06752

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 8902631 A	23-03-1989	CA 1312385 A	05-01-1993
		DE 3889904 D	07-07-1994
		DE 3889904 T	12-01-1995
		EP 0338041 A	25-10-1989
		JP 1502786 T	21-09-1989
		US 5408619 A	18-04-1995
EP 0624964 A	17-11-1994	GB 2278000 A	16-11-1994
		JP 7006066 A	10-01-1995